

Informative Checklist

This document is an informative checklist for the delivery of television programmes as files to SVT

The three *normative* technical specifications are "Technical Specification for the Delivery of Television Programmes as <u>Files</u> to SVT", "Technical Specification for the Delivery of <u>Live</u> Television Programmes to SVT" and "Technical Specification for the Delivery to <u>SVT News and Sports</u>".

The current version of this informative checklist is available via https://b2b.svt.se/program/komplett-leverans/technical-specifications.html.

File Naming

SVT's specific Programme-ID, Episode Number and Programme Title, e.g. PG-1234567-001A-PROGRAMME_TITLE

HD Video Formats

50 Hz motion portrayal: 720p/50 or 1080i/25

25 Hz motion portrayal: 1080p/25

HD Video Codecs

DNxHD 185x, AVC-Intra 100, ProRes 422 HQ or XDCAM HD422

Video Level Tolerance

Expected Y'R'G'B' range (as 8-bit code values): **16-235** Allowed Y'R'G'B' range (as 8-bit code values): **5-246**

Audio Loudness

Dialogue audibility must be ensured, with the minimum of interference from music and sound effects.

Audio mix compliance: EBU R 128.

Programme Loudness: -23.0 LUFS ± 1.0 LU Allowed Maximum True Peak: -1 dBTP Recommended Loudness Range: ≤ 18 LU

Recommended Loudness Range of Dialogue: ≤6 LU

Recommended separation between dialogue and background: ≥8 LU

Audio Channel Allocations

The two preferred channel allocations (of eight options):

EBU Ref Code	Programme Type	Audio channel numbers															
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
R123: 4b	Stereo with M&E	St. L	St. R	St. M&E L	St. M&E R												
R123: 16b	5.1, stereo and M&E	5.1 L	5.1 R	5.1 C	5.1 LFE	5.1 Ls	5.1 Rs	St. L	St. R	5.1 M&E L	5.1 M&E R	5.1 M&E C	5.1 M&E LFE	5.1 M&E Ls	5.1 M&E Rs	St. M&E L	St. M&E R

If possible, we prefer the audio to be delivered as a 3.0 or a 5.1 mix with all the dialogue distributed into the center channel.

Sveriges Television AB, March 2021, v5.1 – Page 1 of 1